SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Tau UV Ink RSC 3 - Orange

Trade name : Orange
Tau UV Ink RSC 3

Product code : 1690367

UFI : MSFF-Q7D7-M00D-W1RJ

Date of issue/Date of revision : 25 January 2026

Version : 2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Printing ink; Printing ink related material; Colorant

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer/ Distributor : Durst Group AG
Julius-Durst-Straße 4
39042 Brixen
Italy
P.: +39 0472 810111
F.: +39 0472 830980

e-mail address of person responsible for this SDS : sds@durst-group.com

1.4 Emergency telephone number

Supplier

Telephone number : (44) 20 3807 3798 (Chemtrec - 24 hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Repr. 2, H361fd
Aquatic Acute 1, H400
Aquatic Chronic 2, H411

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :

SECTION 2: Hazards identification

Signal word : Warning

Hazard statements : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility. Suspected of damaging the unborn child.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : P261 - Avoid breathing vapour. P280 - Wear protective gloves. Wear eye or face protection. P201 - Obtain special instructions before use.

Response : P308 + P313 - IF exposed or concerned: Get medical attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : hexamethylene diacrylate
2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester
2-Phenoxyethyl Acrylate
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
2,4-diethyl-9H-thioxanthen-9-one
2-Propenoic acid, reaction products with dipentaerythritol propoxylated glycerol triacrylated

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

Other hazards which do not result in classification : None known.
This mixture does not contain any substances that are assessed to be endocrine disrupting.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
hexamethylene diacrylate	REACH #: 01-2119484737-22 EC: 235-921-9 CAS: 13048-33-4 Index: 607-109-00-8	50 < 80	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]
2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester	CAS: 86273-46-3	5 < 10	Acute Tox. 4, H302 Skin Sens. 1, H317	[1]
2-Phenoxyethyl Acrylate	REACH #: 01-2119980532-35 EC: 256-360-6 CAS: 48145-04-6	5 < 10	Skin Sens. 1A, H317 Repr. 2, H361fd (oral) Aquatic Chronic 2, H411	[1]
phenyl bis	REACH #:	3 < 5	Skin Sens. 1A, H317	[1]

SECTION 3: Composition/information on ingredients

(2,4,6-trimethylbenzoyl)-phosphine oxide	01-2119489401-38 01-2119936813-33 EC: 423-340-5 CAS: 162881-26-7 Index: 015-189-00-5		Aquatic Chronic 4, H413	
2,4-diethyl-9H-thioxanthen-9-one	REACH #: 01-2120769922-42 EC: 280-041-0 CAS: 82799-44-8	1,0 < 3,0	Skin Sens. 1, H317	[1]
2-hydroxy-1-[4-(4-(2-hydroxy-2-methylpropionyl)phenoxy) phenyl]-2-methyl propan-1-one	REACH #: 01-2120797097-39 EC: 472-110-0 CAS: 71868-15-0	1,0 < 3,0	Aquatic Chronic 2, H411	[1]
2-Propenoic acid, reaction products with dipentaerythritol	REACH #: 01-2119980666-22 CAS: 1384855-91-7	1,0 < 3,0	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412	[1]
propoxylated glycerol triacrylated	REACH #: 01-2119487948-12 EC: 500-114-5 CAS: 52408-84-1	0,25 < 1,0	Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
2,6-di-tert-butyl-p-cresol	REACH #: 01-2119480433-40 01-2119555270-46 01-2119565113-46 EC: 204-881-4 CAS: 128-37-0	0,1 < 0,25	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
octamethylcyclotetrasiloxane	REACH #: 01-2119529238-36 EC: 209-136-7 CAS: 556-67-2 Index: 014-018-00-1	< 0,05	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Chronic 1, H410 (M=10) **See Section 16 for the full text of the H statements declared above.**	[1] [2] [3]

Type

[1] Substance classified with a health or environmental hazard
[2] Substance meets the criteria for PBT
[3] Substance meets the criteria for vPvB
Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact : Remove contact lenses, if present and easy to do. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

SECTION 4: First aid measures

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure.
If splashed in the eyes, the liquid may cause irritation and reversible damage.
The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion may cause nausea, weakness and central nervous system effects.

Contains hexamethylene diacrylate, 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester, 2-phenoxyethyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, 2-Propenoic acid, reaction products with dipentaerythritol, Glycerol, propoxylated, esters with acrylic acid. May produce an allergic reaction.

The following products have sensitising properties: hexamethylene diacrylate, 2-Propenoic acid, 2-[2-(ethenyloxy) ethoxy]ethyl ester, 2-phenoxyethyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, 2,4-diethyl-9H-thioxanthen-9-one, 2-Propenoic acid, reaction products with dipentaerythritol. Cases of hypersensitivity may occur, possibly with cross-sensitisation to other acrylate materials.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to medical doctor : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO_2, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products : Decomposition products may include the following materials:
carbon monoxide
carbon dioxide
smoke
oxides of nitrogen

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

Persons with a history of skin sensitization problems should not be employed in any process in which this product is used, without Personal Protective Equipment measures.

7.1 Precautions for safe handling

Protective measures : Use only in well-ventilated areas. Keep container tightly closed. Keep away from heat, sparks and flame. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Always keep in containers made from the same material as the original one. Avoid exposure during pregnancy. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Comply with the health and safety at work laws. Avoid release to the environment.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 5 – 35 °C. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition - No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Do not reuse container. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E1	100 tonne	200 tonne

7.3 Specific end use(s)

Recommendations : For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
hexamethylene diacrylate	DNEL	Long term Dermal	2.77 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	24.5 mg/m³	Workers	Systemic
2-Propenoic acid, 2-[2-(ethenyloxy) ethoxy]ethyl ester	DNEL	Long term Dermal	0.56 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.97 mg/m³	Workers	Systemic
2-phenoxyethyl acrylate	DNEL	Long term Dermal	3.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Local
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	3.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	7.84 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	7.84 mg/m³	Workers	Systemic
2,4-diethyl-9H-thioxanthen-9-one	DNEL	Long term Dermal	1.46 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	5.14 mg/m³	Workers	Systemic
2-hydroxy-1-[4-(4-(2-hydroxy-2-methylpropionyl)phenoxy)phenyl] -2-methyl propan-1-one	DNEL	Long term Dermal	0.117 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.164 mg/m³	Workers	Systemic
2-Propenoic acid, reaction products with dipentaerythritol	DNEL	Long term Inhalation	1.76 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
Glycerol, propoxylated, esters with acrylic acid	DNEL	Long term Dermal	2.1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	7.4 mg/m³	Workers	Systemic
2,6-di-tert-butyl-p-cresol	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term	1.76 mg/m³	Workers	Systemic

SECTION 8: Exposure controls/personal protection

octamethylcyclotetrasiloxane	DNEL	Inhalation Long term	73 mg/m³	Workers	Local
	DNEL	Inhalation Long term Inhalation	73 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
hexamethylene diacrylate	Fresh water	0.0015 mg/l	-
	Marine water	0.00015 mg/l	-
	Sewage Treatment Plant	2.7 mg/l	-
	Fresh water sediment	0.0243 mg/kg dwt	-
	Marine water sediment	0.00243 mg/kg dwt	-
	Soil	0.00397 mg/kg dwt	-
Glycerol, propoxylated, esters with acrylic acid	Fresh water	0.00574 mg/l	-
	Marine water	0.000574 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	0.01687 mg/kg dwt	-
	Marine water sediment	0.001687 mg/kg dwt	-
	Soil	0.00111 mg/kg dwt	-
	Secondary Poisoning	5.6 mg/kg	-
2,6-di-tert-butyl-p-cresol	Fresh water	4 µg/l	-
	Marine water	0.4 µg/l	-
	Sewage Treatment Plant	100 mg/l	-
	Fresh water sediment	1.29 mg/kg dwt	-
	Soil	1.04 mg/kg dwt	-
	Secondary Poisoning	16.7 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Use safety eyewear designed to protect against splash of liquids. Use eye protection according to EN 166.

Skin protection

Hand protection : Wear suitable gloves tested to EN374. There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

SECTION 8: Exposure controls/personal protection

Gloves : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

"RadTech recommend use of:
-single use: disposable, unpowdered, nitrile gloves: Use for short duration exposures not exceeding 30 minutes, in situations where only splashes are likely. Do not use where mechanical resistance is required or where puncturing or tearing of the gloves is likely to occur. Replace immediately if punctured, degraded or tearing of the gloves has occurred.
-general use: minimum 0.45mm thick, unlined, unpowdered, natural rubber latex-free nitrile gloves: Use for longer duration exposure (up to 4 hours for most UV/EB curing acrylates) or mechanical handling activities. Replace immediately when punctured or when a change of appearance (colour, elasticity, shape) occurs
- heavy duty: unlined, natural rubber latex-free nitrile gloves: Use when handling solvents. Avoid the use of chlorinated solvents and limit the use of ketones (e.g. acetone, MEK, MIBK) and ethyl and butyl acetates, as they may accelerate glove deterioration."

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear protective clothing.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Environmental exposure controls : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Orange.

Odour : Characteristic.

Melting point/freezing point : Not applicable.

Initial boiling point and boiling range : Lowest known value: 132°C (270°F)

Flammability : Not flammable.

Lower and upper explosion limit : Not available.

Flash point : >100°C

Auto-ignition temperature : 235°C (455°F) (hexamethylene diacrylate (13048-33-4))

Decomposition temperature : Not applicable.

SECTION 9: Physical and chemical properties

pH	:	Product is non-polar/aprotic.
Viscosity	:	Not tested
Solubility(ies)	:	
Not available.		
Solubility in water (g/l)	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	:	0.00006 kPa (0.00045 mm Hg) (hexamethylene diacrylate (13048-33-4))
Evaporation rate	:	Not tested
Relative density	:	Not tested
Density	:	1.144 g/cm³ (9.544 lbs/gal)
Vapour density	:	>1 [Air = 1]
Explosive properties	:	Not applicable.
Oxidising properties	:	Not applicable.

9.2 Other information

VOC content	:	0%

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	Hazardous reactions or instability may occur under certain conditions of storage or use.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	This mixture contains materials which are unstable under the following conditions: exposure to heat, strong UV sources. These could cause the product to polymerise exothermically. Unintentional contact with them should be avoided.
10.5 Incompatible materials	:	Keep away from: free radical initiators, peroxides, strong alkalis, reactive metals.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerisation	:	May polymerise on exposure to sunlight.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure.
If splashed in the eyes, the liquid may cause irritation and reversible damage.
The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion may cause nausea, weakness and central nervous system effects.

Contains hexamethylene diacrylate, 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester, 2-phenoxyethyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, 2-Propenoic acid, reaction products with dipentaerythritol, Glycerol, propoxylated, esters with acrylic acid. May produce an allergic reaction.

The following products have sensitising properties: hexamethylene diacrylate, 2-Propenoic acid, 2-[2-(ethenyloxy) ethoxy]ethyl ester, 2-phenoxyethyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, 2,4-diethyl-9H-thioxanthen-9-one, 2-Propenoic acid, reaction products with dipentaerythritol. Cases of hypersensitivity may occur, possibly with cross-sensitisation to other acrylate materials.

Acute toxicity

SECTION 11: Toxicological information

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc.May cause allergic skin reactions with repeated exposure.

Product/ingredient name	Result	Species	Dose	Exposure
hexamethylene diacrylate (13048-33-4)	LD50 Oral	Rat	5 g/kg	-
octamethylcyclotetrasiloxane (556-67-2)	LC50 Inhalation Vapour	Rat	36 g/m³	4 hours
	LD50 Dermal	Rat	1770 mg/kg	-
	LD50 Oral	Rat	1540 mg/kg	-

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Calculated value for the mixture	5010.0	N/A	N/A	N/A	N/A
hexamethylene diacrylate (13048-33-4)	5000	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester	500	N/A	N/A	N/A	N/A
octamethylcyclotetrasiloxane (556-67-2)	N/A	N/A	N/A	36	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure	Observation
hexamethylene diacrylate (13048-33-4)	Skin - Severe irritant	Rabbit -	24 hours 500 mg	-

Skin : The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eyes : The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Respiratory : The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Sensitisation

Skin : The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Respiratory : The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Mutagenicity

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Carcinogenicity

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Reproductive toxicity

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Teratogenicity

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

11.2 Information on other hazards

SECTION 11: Toxicological information

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
octamethylcyclotetrasiloxane (556-67-2)	Chronic NOEC 15 µg/l Fresh water	Daphnia - *Daphnia magna*	48 hours

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

12.2 Persistence and degradability

The product has not been tested. Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

12.3 Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
hexamethylene diacrylate	2.81	-	Low
2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester	1.7	-	Low
phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide	5.77	-	High
2-Propenoic acid, reaction products with dipentaerythritol	-	86.4	Low
Glycerol, propoxylated, esters with acrylic acid	2.52	-	Low
2,6-di-tert-butyl-p-cresol	5.1	-	High
octamethylcyclotetrasiloxane (556-67-2)	6.488	-	High

12.4 Mobility in soil

Soil/water partition coefficient (K_{OC}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
hexamethylene diacrylate (13048-33-4)	No	N/A	N/A	No	N/A	N/A	N/A
2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester	No	N/A	N/A	No	N/A	N/A	N/A
phenyl bis (2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7)	No	N/A	N/A	No	N/A	N/A	N/A
2,4-diethyl-9H-thioxanthen-9-one	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxy-1-[4-(4-(2-hydroxy-2-methylpropionyl)phenoxy) phenyl]-2-methyl propan-1-one	No	N/A	N/A	No	N/A	N/A	N/A

SECTION 12: Ecological information

2-Propenoic acid, reaction products with dipentaerythritol	No	N/A	No	No	No	N/A	No
propoxylated glycerol triacrylated	No	N/A	N/A	No	N/A	N/A	N/A
2,6-di-tert-butyl-p-cresol	No	N/A	N/A	No	N/A	N/A	N/A
octamethylcyclotetrasiloxane (556-67-2)	SVHC (Candidate)	Specified	Specified	Specified	SVHC (Candidate)	Specified	Specified

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Disposal considerations : Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.
If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.
For further information, contact your local waste authority.

European waste catalogue (EWC) (2008/98/EC)

Waste code	Waste designation
08 03 12*	waste ink containing hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.
Empty containers must be scrapped or reconditioned.
Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate; 2-Phenoxyethyl	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate; 2-Phenoxyethyl	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate; 2-Phenoxyethyl	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate; 2-Phenoxyethyl

SECTION 14: Transport information

	Acrylate)	Acrylate)	Acrylate)	Acrylate)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

ADN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
PBT	octamethylcyclotetrasiloxane	Candidate	-	-
vPvB	octamethylcyclotetrasiloxane	Candidate	-	-

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC content : 0%

Ozone depleting substances (2024/590/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code : 4

◤ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Key literature references and sources for data : https://echa.europa.eu/information-on-chemicals
https://echa.europa.eu/information-on-chemicals/registered-substances
https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32020R0878&rid=1
FDS do fornecedor

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361fd	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Training advice : Not available.

Date of printing : 28 January 2026

Date of issue/Date of revision : 25 January 2026

Date of previous issue : 10 January 2026

Version : 2

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

JCUP20002